

FASCO MODEL	HP	VOLTS	RPM	SPD.	AMPS	ROT.	SHAFT DIM.	STACK in./mm	APPL.	CROSS REF.	FIG.	NOTES
K114	1/500	115	1100	1	0.64	CCW	.181 x 1.75	.5/12.7	Refrigeration Fan	Hussman 301-5734	A	7
K628	1/200	208-230	3000	1	0.25	CW	1/4 x 1-1/2	.75/19.0			B	8
K102	1/200	115	1100	1	0.64	CW	.181 x 1.5	.562/14.2	Wall Heater	Fasco 1235-0007 or 7102-0003	A	7,9
K120	1/200	115	3000	2	.4-.25	CW	.217 x 1.55	.562/14.2	Ductless Rangehood	Arrowhood 602, 605, 607, UPPCO 37F2M	C	7,10
K614	1/150	115	3000	1	0.6	CW	.217 x 1.625	.562/14.2	Vent Fan	General Replacement	D	7
K673	1/150	115	3000	2	.5-.35	CCW	.1875 x 1.75	.625/15.8	Vent Fan	EM673	E	8,10
K670	1/150	115	3000	1	0.5	CCW	.1875 x 1.75	.625/15.8	Vent Fan	GEM EM 670, ACME AM-4670, SUPCO SM-670, MARS 90971	E	8
K130	1/150	115	3000	1	0.43	CW	.181 x 1	.625/15.8	Vent Fan	Standard Replacement 5/8" STACK	F	7,9
K101	1/150	230	1260	1	0.58	CCW	.217 x 1.34	1.25/31.7	Wall Heater	Fasco 8767-8036 or 7102-0001	G	7
K672	1/150	240	3000	1	0.25	CCW	.1875 x 1.75	.625/15.8	Vent Fan	GEM EM 672, Acme 602/702 WESTWARD 14005	E	8
K683	1/150	240	3000	1	0.25	CW	.1875 x 1.75	.875/22.2	Vent Fan	GEM EM683, WESTWARD 14025	H	7
K111	1/120	115	3000	1	1.1	CCW	.217 x 1.94	.562/14.2	Vent Fan	NUTONE 65878, WESTWARD VFM 100	I	7
K100	1/100	115	2750	1	0.71	CW	.181 x 1.11	.625/15.8	Vent Fan	Fasco 0648-0027, 642, 643, 645, 646, 647, A647, B647, 648S, 664, A664, 667, A667, B667 and many others	J	7,9
K611	1/100	115	3000	1	0.67	CCW	.25 x 2.45	.75/19.0	Vent Fan	BROAN 162	K	7
K115	1/100	120	3000	1	0.64	CW	.217 x 1.75	.75/19.0	Heater	NUTONE 66582, 9605-N, 9665-N, 9093-N WESTWARD VFM 104	L	7
K629	1/85	115	2950	1	0.67	CW	1/4 x 1-1/8	1.00/25.4			M	8
K109	1/75	115	3000	1	0.9	CCW	.217 x 2.37	.75/19.0	Vent Fan	NUTONE C-68626, C-68627, WESTWARD VFM 106	N	7
K110	1/75	115	3000	1	0.9	CCW	.217 x 2.37	.75/19.0	Vent Fan	BROAN 99-08-0165, 670A	N	7,11
K113	1/70	115	3000	1	1.2	CCW	.217 x 1.15	.75/19.0	Vent Fan	NUTONE 63675, 9605-N, 9665-N, WESTWARD VFM 103	O	7

NOTES: 7: Packed 6 per carton 8: Packed 1 per carton 9: Use Fan Blades with round hub I.D. 10: Two Speed Motor 11: K110 has maximum flat length



FIG. A K114, K102



FIG. B K628



FIG. C K120



FIG. D K614



FIG. E K673, K670, K672



FIG. F K130



FIG. G K101



FIG. H K683



FIG. I K111



FIG. J K100



FIG. K K611



FIG. L K115



FIG. M K629



FIG. N K109, K110



FIG. O K113

Thermally protected • UL recognized • CSA or ULc certified
NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



FASCO MODEL	HP	VOLTS	RPM	SPD.	AMPS	ROT.	SHAFT DIM.	STACK in./mm	APPL.	CROSS REF.	FIG.	NOTES
K612	1/65	115	3000	1	0.8	CW	.25 x 2.7	1.00/25.4	Vent Fan	UPPCO 99080145, BROAN 162	A	7
K610	1/60	115	3000	2	.88-.68	CCW	.217 x 1.3	1.00/25.4	Rangehood	RO TOM R610 ELECTROHOME 2858-207-002, BROAN 30080011	B	7,10
K112	1/50	115	3000	2	1-.5	CW	.217 x 1.46	1.00/25.4	Rangehood	NUTONE 52367, WESTWARD VFM 101	C	7,10
K161	1/50	115	3000	1	1.05	CCW	.217 x 1.21	1.00/25.4	Icemaker	AEROVOX S11000017, MATHIESEN	D	7

NOTES: 7: Packed 6 per carton 10: Two Speed Motor

Fan Blades Used with K-Line Motors

FASCO MODEL	ROT.	DESCRIPTION	BORE DIA.	FAN DIA.	FITS SHAFT DIA.	FIG.
K-FAN4032		"D" shaped hub	.2178	4 5/8		E
K-FAN4031		Round bore hub	.1811	4 5/8		E
K-FAN6009	CW	"D" shaped hub	.2178	6 5/8		F
K-FAN6010	CW	Round bore hub	.1811	4		G
K-FAN6012	CW	Round bore hub	.1811	3 1/2		H
K-FAN6013	CCW	Round bore hub	.1811	5 1/2		I
K-FAN6011	CW	Round bore hub	.1811	4		J
K-FAN6046	CCW	Round bore hub	.1811	5 1/2		F
K-NUT		Push nut			.1811	K
K-NUT6002		Push nut			.2178	K



FIG. A **K612**



FIG. B **K610**



FIG. C **K112**




FIG. D **K161**



FIG. E **K-FAN4032, K-FAN4031**



FIG. F **K-FAN6009, K-FAN6046**



FIG. G **K-FAN6010**



FIG. H **K-FAN6012**



FIG. I **K-FAN6013**



FIG. J **K-FAN6011**



FIG. K **K-NUT, K-NUT6002**