

FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.	RING TO RING DIM.	FIG.	NOTES
48 FRAME													
D6002	SPLIT PHASE	1/4	115/230	1725	1	5.2-2.6	Open Drip Proof	REV	BALL	1/2 x 1-1/2	7.435	A	126,127,128
D6004	SPLIT PHASE	1/3	115/230	1725	1	6.2-3.1	Open Drip Proof	REV	BALL	1/2 x 1-1/2	7.935	A	126,127,128
D6006	SPLIT PHASE	1/2	115/230	1725	1	8.6-4.3	Open Drip Proof	REV	BALL	1/2 x 1-1/2	8.435	A	126,127,128
56 FRAME													
D6082	CAPACITOR START	1/3	115/208-230	1725	1	6.2-3.1	Open Drip Proof	REV	BALL	5/8 x 2	7.945	B	127,128
D6084	CAPACITOR START	1/2	115/208-230	1725	1	8.8-4.4	Open Drip Proof	REV	BALL	5/8 x 2	8.445	B	127,128
D6066	CAPACITOR START	3/4	115/208-230	3450	1	9.6-4.8	Open Drip Proof	REV	BALL	5/8 x 2	9.445	B	127,128
D6086	CAPACITOR START	3/4	115/208-230	1725	1	10.8-5.4	Open Drip Proof	REV	BALL	5/8 x 2	9.445	B	127,128
D6068	CAPACITOR START	1	115/208-230	3450	1	12-6	Open Drip Proof	REV	BALL	5/8 x 2	9.445	C	127,128
D6088	CAPACITOR START	1	115/208-230	1725	1	12.8-6.4	Open Drip Proof	REV	BALL	5/8 x 2	9.445	C	127,128
D6070	CAPACITOR START	1.5	115/208-230	3450	1	17.2-8.6	Open Drip Proof	REV	BALL	5/8 x 2	9.445	C	127,128
D6090	CAPACITOR START	1.5	115/208-230	1725	1	14.4-7.2	Open Drip Proof	REV	BALL	5/8 x 2	10.445	C	127,128,129
D6073	CAPACITOR START	2	115/208-230	3450	1	24-12	Open Drip Proof	REV	BALL	5/8 x 2	10.445	C	127,128
D6093	CAPACITOR START	2	115/208-230	1725	1	20-10	Open Drip Proof	REV	BALL	5/8 x 2	10.945	C	127,128,129
D6622	THREE PHASE	1/3	208-230/460	1725	1	1.6-8	Open Drip Proof	REV	BALL	5/8 x 2	8.445	D	127,128
D6624	THREE PHASE	1/2	208-230/460	1725	1	2-1	Open Drip Proof	REV	BALL	5/8 x 2	8.945	D	127,128
D6626	THREE PHASE	3/4	208-230/460	1725	1	2.8-1.4	Open Drip Proof	REV	BALL	5/8 x 2	9.945	D	127,128
D6628	THREE PHASE	1	208-230/460	1725	1	3.4-1.7	Open Drip Proof	REV	BALL	5/8 x 2	9.445	E	127,128
D6630	THREE PHASE	1.5	208-230/460	1725	1	4.6-2.3	Open Drip Proof	REV	BALL	5/8 x 2	9.945	E	127,128
D6631	THREE PHASE	2	208-230/460	1725	1	6.2-3.1	Open Drip Proof	REV	BALL	5/8 x 2	9.945	E	127,128,129
D6633	THREE PHASE	3	208-230/460	1725	1	8-4	Open Drip Proof	REV	BALL	7/8 x 2-3/8	11.445	E	127,128,130
56Y FRAME													
D6608	THREE PHASE	1	208-230/460	1140	1	4-2	Open Vent.	REV	BALL	5/8 x 3-3/4		F	131,132
D6610	THREE PHASE	1.5	208-230/460	1140	1	5.6-2.8	Open Vent.	REV	BALL	5/8 x 3-3/4		F	131,132

NOTES: 126: Belted Fan & Blower Motor 127: Continuous duty 128: Resilient base 129: 56H Mounting 130: 145T Frame 131: NEMA 56Y Frame 132: Condenser Fan Motor



FIG. A D6002, D6004, D6006



FIG. B D6082, D6084, D6066, D6086



FIG. C D6068, D6088, D6070, D6090, D6073, D6093



FIG. D D6622, D6624, D6626



FIG. E D6628, D6630, D6631, D6633



FIG. F D6608, D6610