



## Product Applications

HVAC Equipment

Appliances

Office Equipment

## Product Features

Proven IEC-252 Class B Compliant 10,000 Hour Reliability

Pressure Sensitive Interrupter (PSI)

Manufactured in North America with over 50 years of engineering experience

## Product Benefits

Significantly lower cost than the Regal Beloit Long Life brand

Quality parts eliminate repeat visits, save fuel, and reduce overall costs

### 370VAC OVAL Motor Run Capacitors

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C3S2	2.0	-	370	1.25	1.56	-40°C to 70°C
C3S3	3.0	-	370	1.25	1.56	-40°C to 70°C
C3S4	4.0	-	370	1.25	1.56	-40°C to 70°C
C3S5	5.0	-	370	1.25	1.56	-40°C to 70°C
C3S6	6.0	-	370	1.25	2.12	-40°C to 70°C
C3S7.5	7.5	-	370	1.25	2.12	-40°C to 70°C
C3S10	10.0	-	370	1.25	2.88	-40°C to 70°C
C3S12.5	12.5	-	370	1.25	2.88	-40°C to 70°C
C3S15	15.0	-	370	1.25	2.88	-40°C to 70°C
C3S17.5	17.5	-	370	1.25	3.88	-40°C to 70°C
C3S20	20.0	-	370	1.25	3.88	-40°C to 70°C
C3S25	25.0	-	370	1.25	3.88	-40°C to 70°C
C3S30	30.0	-	370	1.25	4.75	-40°C to 70°C
C3S35	35.0	-	370	1.25	4.75	-40°C to 70°C
C3S40	40.0	-	370	1.75	3.88	-40°C to 70°C
C3S45	45.0	-	370	1.75	3.88	-40°C to 70°C
C3S50	50.0	-	370	1.75	3.88	-40°C to 70°C
C3S60	60.0	-	370	1.75	4.75	-40°C to 70°C

### 440VAC OVAL Motor Run Capacitors

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C4S5	5.0	-	440	1.25	2.12	-40°C to 70°C
C4S7.5	7.5	-	440	1.25	2.88	-40°C to 70°C
C4S10	10.0	-	440	1.25	2.88	-40°C to 70°C
C4S12.5	12.5	-	440	1.25	3.88	-40°C to 70°C
C4S15	15.0	-	440	1.25	4.75	-40°C to 70°C
C4S17.5	17.5	-	440	1.25	4.75	-40°C to 70°C
C4S20	20.0	-	440	1.25	4.75	-40°C to 70°C
C4S25	25.0	-	440	1.25	4.75	-40°C to 70°C
C4S30	30.0	-	440	1.75	3.88	-40°C to 70°C
C4S35	35.0	-	440	1.75	3.88	-40°C to 70°C
C4S40	40.0	-	440	1.75	3.88	-40°C to 70°C
C4S45	45.0	-	440	1.75	4.75	-40°C to 70°C
C4S50	50.0	-	440	1.75	4.75	-40°C to 70°C
C4S60	60.0	-	440	2.00	4.25	-40°C to 70°C

### 370VAC ROUND Motor Run Capacitors

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C3RS5	5.0	-	370	1.75	2.88	-40°C to 70°C
C3RS7.5	7.5	-	370	1.75	2.88	-40°C to 70°C
C3RS10	10.0	-	370	1.75	2.88	-40°C to 70°C
C3RS15	15.0	-	370	1.75	2.88	-40°C to 70°C
C3RS17.5	17.5	-	370	1.75	2.88	-40°C to 70°C
C3RS20	20.0	-	370	1.75	2.88	-40°C to 70°C
C3RS25	25.0	-	370	1.75	2.88	-40°C to 70°C
C3RS30	30.0	-	370	1.75	3.88	-40°C to 70°C
C3RS35	35.0	-	370	1.75	3.88	-40°C to 70°C
C3RS40	40.0	-	370	1.75	3.88	-40°C to 70°C
C3RS45	45.0	-	370	1.75	4.75	-40°C to 70°C
C3RS50	50.0	-	370	1.75	4.75	-40°C to 70°C
C3RS55	55.0	-	370	1.75	4.75	-40°C to 70°C
C3RS60	60.0	-	370	1.75	4.75	-40°C to 70°C
C3RS70	70.0	-	370	2.50	4.75	-40°C to 70°C
C3RS80	80.0	-	370	2.50	4.75	-40°C to 70°C

### 440VAC ROUND Motor Run Capacitors

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C4RS5	5.0	-	440	1.75	2.88	-40°C to 70°C
C4RS7.5	7.5	-	440	1.75	2.88	-40°C to 70°C
C4RS10	10.0	-	440	1.75	2.88	-40°C to 70°C
C4RS12.5	12.5	-	440	1.75	2.88	-40°C to 70°C
C4RS15	15.0	-	440	1.75	2.88	-40°C to 70°C
C4RS20	20.0	-	440	1.75	2.88	-40°C to 70°C
C4RS25	25.0	-	440	1.75	3.88	-40°C to 70°C
C4RS30	30.0	-	440	1.75	3.88	-40°C to 70°C
C4RS35	35.0	-	440	2.00	3.88	-40°C to 70°C
C4RS40	40.0	-	440	1.75	4.75	-40°C to 70°C
C4RS45	45.0	-	440	2.00	3.88	-40°C to 70°C
C4RS50	50.0	-	440	2.00	5.75	-40°C to 70°C
C4RS55	55.0	-	440	2.50	4.75	-40°C to 70°C
C4RS60	60.0	-	440	2.50	4.75	-40°C to 70°C
C4RS70	70.0	-	440	2.50	4.75	-40°C to 70°C
C4RS80	80.0	-	440	2.50	5.75	-40°C to 70°C

**370VAC DUAL OVAL Motor Run Capacitors**

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C3D1010	10.0	10.0	370	1.75	2.12	-40°C to 70°C
C3D155	15.0	5.0	370	1.75	2.88	-40°C to 70°C
C3D157.5	15.0	7.5	370	1.75	2.88	-40°C to 70°C
C3D1510	15.0	10.0	370	1.75	2.88	-40°C to 70°C
C3D205	20.0	5.0	370	1.75	2.88	-40°C to 70°C
C3D207.5	20.0	7.5	370	1.75	2.88	-40°C to 70°C
C3D2010	20.0	10.0	370	1.75	3.88	-40°C to 70°C
C3D255	25.0	5.0	370	1.75	2.88	-40°C to 70°C
C3D257.5	25.0	7.5	370	1.75	2.88	-40°C to 70°C
C3D2510	25.0	10.0	370	1.75	2.88	-40°C to 70°C
C3D305	30.0	5.0	370	1.75	3.88	-40°C to 70°C
C3D307.5	30.0	7.5	370	1.75	3.88	-40°C to 70°C
C3D3010	30.0	10.0	370	1.75	3.88	-40°C to 70°C
C3D355	35.0	5.0	370	1.75	3.88	-40°C to 70°C
C3D357.5	35.0	7.5	370	1.75	3.88	-40°C to 70°C
C3D3510	35.0	10.0	370	1.75	3.88	-40°C to 70°C
C3D405	40.0	5.0	370	1.75	3.88	-40°C to 70°C
C3D407.5	40.0	7.5	370	1.75	3.88	-40°C to 70°C
C3D4010	40.0	10.0	370	1.75	3.88	-40°C to 70°C
C3D455	45.0	5.0	370	1.75	3.88	-40°C to 70°C
C3D457.5	45.0	7.5	370	1.75	3.88	-40°C to 70°C
C3D4510	45.0	10.0	370	1.75	3.88	-40°C to 70°C
C3D505	50.0	5.0	370	1.75	4.75	-40°C to 70°C
C3D507.5	50.0	7.5	370	1.75	4.75	-40°C to 70°C
C3D5010	50.0	10.0	370	2.00	4.75	-40°C to 70°C

**440VAC DUAL OVAL Motor Run Capacitors**

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C4D1010	10.0	10.0	440	1.75	2.88	-40°C to 70°C
C4D155	15.0	5.0	440	1.75	2.88	-40°C to 70°C
C4D157.5	15.0	7.5	440	1.75	2.88	-40°C to 70°C
C4D1510	15.0	10.0	440	1.75	3.88	-40°C to 70°C
C4D205	20.0	5.0	440	1.75	2.88	-40°C to 70°C
C4D207.5	20.0	7.5	440	1.75	3.88	-40°C to 70°C
C4D2010	20.0	10.0	440	1.75	3.88	-40°C to 70°C
C4D255	25.0	5.0	440	1.75	3.88	-40°C to 70°C
C4D257.5	25.0	7.5	440	1.75	3.88	-40°C to 70°C
C4D2510	25.0	10.0	440	1.75	4.75	-40°C to 70°C
C4D305	30.0	5.0	440	1.75	3.88	-40°C to 70°C
C4D307.5	30.0	7.5	440	1.75	3.88	-40°C to 70°C
C4D3010	30.0	10.0	440	1.75	4.75	-40°C to 70°C
C4D355	35.0	5.0	440	1.75	4.75	-40°C to 70°C
C4D357.5	35.0	7.5	440	1.75	4.75	-40°C to 70°C
C4D3510	35.0	10.0	440	1.75	4.75	-40°C to 70°C
C4D405	40.0	5.0	440	1.75	4.75	-40°C to 70°C
C4D407.5	40.0	7.5	440	1.75	4.75	-40°C to 70°C
C4D4010	40.0	10.0	440	2.00	4.75	-40°C to 70°C
C4D455	45.0	5.0	440	1.75	4.75	-40°C to 70°C
C4D457.5	45.0	7.5	440	2.00	4.75	-40°C to 70°C
C4D4510	45.0	10.0	440	1.75	4.75	-40°C to 70°C
C4D505	50.0	5.0	440	2.00	5.25	-40°C to 70°C
C4D507.5	50.0	7.5	440	2.00	5.25	-40°C to 70°C
C4D5010	50.0	10.0	440	2.00	5.25	-40°C to 70°C

**370VAC DUAL ROUND Motor Run Capacitors**

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C3DR155	15.0	5.0	370	2.00	2.88	-40°C to 70°C
C3DR157.5	15.0	7.5	370	2.00	2.88	-40°C to 70°C
C3DR1510	15.0	10.0	370	2.00	2.88	-40°C to 70°C
C3DR205	20.0	5.0	370	2.00	2.88	-40°C to 70°C
C3DR207.5	20.0	7.5	370	2.00	2.88	-40°C to 70°C
C3DR2010	20.0	10.0	370	2.00	2.88	-40°C to 70°C
C3DR255	25.0	5.0	370	2.00	2.88	-40°C to 70°C
C3DR257.5	25.0	7.5	370	2.00	2.88	-40°C to 70°C
C3DR2510	25.0	10.0	370	2.00	2.88	-40°C to 70°C
C3DR305	30.0	5.0	370	2.00	2.88	-40°C to 70°C
C3DR307.5	30.0	7.5	370	2.00	3.88	-40°C to 70°C
C3DR3010	30.0	10.0	370	2.00	3.88	-40°C to 70°C
C3DR355	35.0	5.0	370	2.00	3.88	-40°C to 70°C
C3DR357.5	35.0	7.5	370	2.00	3.88	-40°C to 70°C
C3DR3510	35.0	10.0	370	2.00	3.88	-40°C to 70°C
C3DR405	40.0	5.0	370	2.00	3.88	-40°C to 70°C
C3DR407.5	40.0	7.5	370	2.00	3.88	-40°C to 70°C
C3DR4010	40.0	10.0	370	2.00	3.88	-40°C to 70°C
C3DR455	45.0	5.0	370	2.00	3.88	-40°C to 70°C
C3DR457.5	45.0	7.5	370	2.00	3.88	-40°C to 70°C
C3DR4510	45.0	10.0	370	2.00	4.75	-40°C to 70°C
C3DR505	50.0	5.0	370	2.00	3.88	-40°C to 70°C
C3DR507.5	50.0	7.5	370	2.00	4.75	-40°C to 70°C
C3DR5010	50.0	10.0	370	2.00	4.75	-40°C to 70°C
C3DR555	55.0	5.0	370	2.50	3.88	-40°C to 70°C
C3DR557.5	55.0	7.5	370	2.50	3.88	-40°C to 70°C
C3DR5510	55.0	10.0	370	2.50	3.88	-40°C to 70°C
C3DR605	60.0	5.0	370	2.50	3.88	-40°C to 70°C
C3DR607.5	60.0	7.5	370	2.50	4.75	-40°C to 70°C
C3DR6010	60.0	10.0	370	2.50	4.75	-40°C to 70°C
C3DR705	70.0	5.0	370	2.50	4.75	-40°C to 70°C
C3DR707.5	70.0	7.5	370	2.50	4.75	-40°C to 70°C
C3DR7010	70.0	10.0	370	2.50	4.75	-40°C to 70°C
C3DR805	80.0	5.0	370	2.50	4.75	-40°C to 70°C
C3DR807.5	80.0	7.5	370	2.50	4.75	-40°C to 70°C
C3DR8010	80.0	10.0	370	2.50	4.75	-40°C to 70°C

**440VAC DUAL ROUND Motor Run Capacitors**

FDC PART NBR	UF1	UF2	VAC	Cap Dia.	Case Height	Op Temp.
C4DR155	15.0	5.0	440	2.00	2.88	-40°C to 70°C
C4DR157.5	15.0	7.5	440	2.00	3.88	-40°C to 70°C
C4DR1510	15.0	10.0	440	2.00	3.88	-40°C to 70°C
C4DR205	20.0	5.0	440	2.00	2.88	-40°C to 70°C
C4DR207.5	20.0	7.5	440	2.00	3.88	-40°C to 70°C
C4DR2010	20.0	10.0	440	2.00	3.88	-40°C to 70°C
C4DR255	25.0	5.0	440	2.00	3.88	-40°C to 70°C
C4DR257.5	25.0	7.5	440	2.00	3.88	-40°C to 70°C
C4DR2510	25.0	10.0	440	2.00	3.88	-40°C to 70°C
C4DR305	30.0	5.0	440	2.00	3.88	-40°C to 70°C
C4DR307.5	30.0	7.5	440	2.00	3.88	-40°C to 70°C
C4DR3010	30.0	10.0	440	2.00	3.88	-40°C to 70°C
C4DR355	35.0	5.0	440	2.00	4.75	-40°C to 70°C
C4DR357.5	35.0	7.5	440	2.00	4.75	-40°C to 70°C
C4DR3510	35.0	10.0	440	2.50	3.88	-40°C to 70°C
C4DR405	40.0	5.0	440	2.50	2.88	-40°C to 70°C
C4DR407.5	40.0	7.5	440	2.00	4.75	-40°C to 70°C
C4DR4010	40.0	10.0	440	2.00	4.75	-40°C to 70°C
C4DR455	45.0	5.0	440	2.50	3.88	-40°C to 70°C
C4DR457.5	45.0	7.5	440	2.50	3.88	-40°C to 70°C
C4DR4510	45.0	10.0	440	2.50	3.88	-40°C to 70°C
C4DR505	50.0	5.0	440	2.50	4.25	-40°C to 70°C
C4DR507.5	50.0	7.5	440	2.50	4.75	-40°C to 70°C
C4DR5010	50.0	10.0	440	2.50	4.75	-40°C to 70°C
C4DR555	55.0	5.0	440	2.50	4.75	-40°C to 70°C
C4DR557.5	55.0	7.5	440	2.50	4.75	-40°C to 70°C
C4DR5510	55.0	10.0	440	2.50	4.75	-40°C to 70°C
C4DR605	60.0	5.0	440	2.50	4.75	-40°C to 70°C
C4DR607.5	60.0	7.5	440	2.50	4.75	-40°C to 70°C
C4DR6010	60.0	10.0	440	2.50	4.75	-40°C to 70°C
C4DR705	70.0	5.0	440	2.50	5.25	-40°C to 70°C
C4DR707.5	70.0	7.5	440	2.50	4.75	-40°C to 70°C
C4DR7010	70.0	10.0	440	2.50	4.75	-40°C to 70°C
C4DR805	80.0	5.0	440	2.50	4.75	-40°C to 70°C
C4DR807.5	80.0	7.5	440	2.50	4.75	-40°C to 70°C
C4DR8010	80.0	10.0	440	2.50	4.75	-40°C to 70°C



For more information go to:  
[www.PROLINEcapacitors.com](http://www.PROLINEcapacitors.com)

1401 East North Street  
Eldon, MO 65026  
1-800-325-8313  
Fax 1-800-352-7207  
[www.fasco.com](http://www.fasco.com)

\* IEC 252 Class B Industry Reliability Standard

6439FS-SK-5k-5/09-RG

