



FASCO MODEL	WATT RATING	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	"A" DIM.	MATERIAL	THERMAL PROTECTION	THREADED SHAFT	FIG.	NOTES
D550	2	115	1550	1	0.24	Totally Encl.	CW	SLV	2.37	Aluminum	Impedence	1/4 - 20	A	12,13,14
D551	2	115	1550	1	0.24	Totally Encl.	CCW	SLV	2.37	Aluminum	Impedence	1/4 - 20	A	12,13,14
D552	2	230	1550	1	0.12	Totally Encl.	CW	SLV	2.37	Aluminum	Impedence	1/4 - 20	A	12,13,14
D553	2	230	1550	1	0.12	Totally Encl.	CCW	SLV	2.37	Aluminum	Impedence	1/4 - 20	A	12,13,14
D554	4	115	1550	1	0.34	Totally Encl.	CW	SLV	2.42	Aluminum	Impedence	1/4 - 20	A	12,13,14
D555	4	115	1550	1	0.34	Totally Encl.	CCW	SLV	2.42	Aluminum	Impedence	1/4 - 20	A	12,13,14
D556	4	230	1550	1	0.16	Totally Encl.	CW	SLV	2.42	Aluminum	Impedence	1/4 - 20	A	12,13,14
D557	4	230	1550	1	0.16	Totally Encl.	CCW	SLV	2.42	Aluminum	Impedence	1/4 - 20	A	12,13,14
D582	5	115	1550	1	0.35	Totally Encl.	CW	SLV	2.6	Aluminum	Impedence	1/4 - 20	A	12,13,14
D583	5	115	1550	1	0.35	Totally Encl.	CCW	SLV	2.6	Aluminum	Impedence	1/4 - 20	A	12,13,14
D558	6	115	1550	1	0.42	Totally Encl.	CW	SLV	2.61	Aluminum	Impedence	1/4 - 20	A	12,13,14
D559	6	115	1550	1	0.42	Totally Encl.	CCW	SLV	2.61	Aluminum	Impedence	1/4 - 20	A	12,13,14
D560	6	230	1550	1	0.21	Totally Encl.	CW	SLV	2.61	Aluminum	Impedence	1/4 - 20	A	12,13,14
D561	6	230	1550	1	0.21	Totally Encl.	CCW	SLV	2.61	Aluminum	Impedence	1/4 - 20	A	12,13,14
D562	9	115	1550	1	0.55	Totally Encl.	CW	SLV	2.65	Aluminum	Auto Reset	1/4 - 20	A	12,13,14
D563	9	115	1550	1	0.55	Totally Encl.	CCW	SLV	2.65	Aluminum	Auto Reset	1/4 - 20	A	12,13,14
D564	9	230	1550	1	0.33	Totally Encl.	CW	SLV	2.65	Aluminum	Auto Reset	1/4 - 20	A	12,13,14
D565	9	230	1550	1	0.33	Totally Encl.	CCW	SLV	2.65	Aluminum	Auto Reset	1/4 - 20	A	12,13,14
D566	16	115	1550	1	1.1	Totally Encl.	CW	SLV	3.34	Iron	Auto Reset	1/4 - 20	B	12,13,14
D567	16	115	1550	1	1.1	Totally Encl.	CCW	SLV	3.34	Iron	Auto Reset	1/4 - 20	B	12,13,14
D568	16	230	1550	1	0.6	Totally Encl.	CW	SLV	3.34	Iron	Auto Reset	1/4 - 20	B	12,13,14
D569	16	230	1550	1	0.6	Totally Encl.	CCW	SLV	3.34	Iron	Auto Reset	1/4 - 20	B	12,13,14
D570	25	115	1550	1	1.2	Totally Encl.	CW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D571	25	115	1550	1	1.2	Totally Encl.	CCW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D572	25	230	1550	1	0.66	Totally Encl.	CW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D573	25	230	1550	1	0.66	Totally Encl.	CCW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D574	35	115	1550	1	1.5	Totally Encl.	CW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D575	35	115	1550	1	1.5	Totally Encl.	CCW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D576	35	230	1550	1	0.7	Totally Encl.	CW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D577	35	230	1550	1	0.7	Totally Encl.	CCW	SLV	3.6	Iron	Auto Reset	1/4 - 20	C	12,13,14
D578	50	115	1550	1	1.8	Open Vent.	CW	SLV	4.67	Iron	Auto Reset	3/8 x 1-1/2	D	13,14
D579	50	115	1550	1	1.8	Open Vent.	CCW	SLV	4.67	Iron	Auto Reset	3/8 x 1-1/2	D	13,14
D580	50	230	1550	1	0.9	Open Vent.	CW	SLV	4.67	Iron	Auto Reset	3/8 x 1-1/2	D	13,14
D581	50	230	1550	1	0.9	Open Vent.	CCW	SLV	4.67	Iron	Auto Reset	3/8 x 1-1/2	D	13,14

NOTES: 12: Speed nut and vibration damper included 13: All mounting holes drilled and tapped 14: Individually boxed



FIG. A D550, D551, D552, D553, D554, D555, D556, D557, D582, D583, D558, D559, D560, D561, D562, D563, D564, D565




FIG. B D566, D567, D568, D569



FIG. C D570, D571, D572, D573, D574, D575, D576, D577



FIG. D D578, D579, D580, D581



Thermally protected • UL recognized • CSA or ULc certified  
 NOTE: Rotation is determined by looking at lead end (unit bearing motors this page only).